



GRiD 9161U Rackmount

Main Features

- VGA and DVI-D Display Support
- Intel® Core i3 Processor
- Up to 16GB Memory
- Connectors and Interfaces Fully Customisable
- Encrypted Drive Compatible
- Qualified for Tempest Environments

Technical Specification

GRiD

RUGGED, CONFIGURABLE COMPUTING



WWW.GRIDUK.COM



GRID-SALES@GRIDUK.COM



+44 (0) 1628 810 230

Internal Specification	
Processor	Intel® Core™ i3-3220, 3.3 GHz
Chipset	Intel® H61 express chipset
Memory	Dual-Channel DDR3 1600/1333 MHz, up to 16GB
Graphics	Intel® HD Graphics
BIOS	AMIBIOS 64Mb SPI BIOS
Storage	Up to 960GB Fixed Solid State Drive Encryption available
ROM	Optional DVD +/- RW
Operating System	Microsoft Windows Linux
Expansion	Up to 2 x 32bit PCI Slots
Display	External Analogue up to 4096 x 2304 (4K)
Keyboard	None
Mouse	None
Power	110V to 240V AC switch mode power supply
Interfaces	User Defined (Interfaces are configurable to suit each application. Please speak to us about your requirements)

Environmental Specification	
EMC	DEF STAN 59-411 MIL-STD-461
Environmental	DEF STAN 00-35 MIL-STD-810
TEMPEST	SDIP-27
Operating Temperature	0°C to +60°C
Humidity	0-95% Non-condensing
Dimensions (WxDxH)	483 x 500 x 44mm
Weight	7.5Kg



GRiD

RUGGED, CONFIGURABLE COMPUTING

